


FINE TUNE YOUR PERFORMANCE

RECOMMENDED PRESSURE CHART



POWER IS NOTHING WITHOUT CONTROL

23-622 700x23c		25-622 700x25c		28-622 700x28c	
Rider weight (kg/lbs)	Pressure (bar/psi)	Rider weight (kg/lbs)	Pressure (bar/psi)	Rider weight (kg/lbs)	Pressure (bar/psi)
≤ 51 kg ≤ 112 lbs	6,7 bar 95 psi	≤ 48 kg ≤ 106 lbs	6 bar 85 psi	≤ 65 kg ≤ 143 lbs	6 bar 85 psi
52 > 60 kg 113 > 133 lbs	7 bar 100 psi	49 > 56 kg 107 > 123 lbs	6,3 bar 90 psi	66 > 78 kg 144 > 172 lbs	6,3 bar 90 psi
61 > 68 kg 134 > 150 lbs	7,3 bar 105 psi	57 > 63 kg 124 > 139 lbs	6,7 bar 95 psi	79 > 89 kg 173 > 196 lbs	6,7 bar 95 psi
69 > 76 kg 151 > 168 lbs	7,7 bar 110 psi	64 > 72 kg 140 > 159 lbs	7 bar 100 psi	90 > 103 kg 197 > 227 lbs	7 bar 100 psi
77 > 84 kg 169 > 185 lbs	8 bar 115 psi	73 > 86 kg 160 > 190 lbs	7,3 bar 105 psi	104 > 120 kg 228 > 265 lbs	7,3 bar 105 psi
85 > 92 kg 186 > 203 lbs	8,3 bar 120 psi	≥ 87 kg ≥ 191 lbs	7,7 bar 110 psi	≥ 121 kg ≥ 266 lbs	7,7 bar 110 psi
≥ 93 kg ≥ 204 lbs	8,7 bar 125 psi				

Cinturato™ VELO									
TUBELESS READY									
24-622 700x24c		26-622 700x26c		28-622 700x28c		32-622 700x32c		35-622 700x35c	
Rider weight (kg/lbs)	Pressure (bar/psi)	Rider weight (kg/lbs)	Pressure (bar/psi)	Rider weight (kg/lbs)	Pressure (bar/psi)	Rider weight (kg/lbs)	Pressure (bar/psi)	Rider weight (kg/lbs)	Pressure (bar/psi)
< 45 kg ≤ 115 lbs	5,5 bar 80 psi	≤ 44 kg 118 > 132 lbs	4,7 bar 65 psi	≤ 48 kg ≤ 97 lbs	4,3 bar 60 psi	≤ 44 kg ≤ 106 lbs	3,5 bar 51 psi	≤ 44 kg ≤ 106 lbs	3 bar 44 psi
45 ÷ 52 kg 116 > 134 lbs	5,8 bar 84 psi	45 ÷ 53 kg 133 > 150 lbs	5 bar 70 psi	49 ÷ 55 kg 98 > 117 lbs	4,7 bar 65 psi	44 ÷ 49 kg 107 > 121 lbs	3,8 bar 55 psi	45 ÷ 49 kg 107 > 121 lbs	3,3 bar 48 psi
53 ÷ 60 kg 135 > 163 lbs	6 bar 87 psi	54 ÷ 63 kg 151 > 174 lbs	5,3 bar 75 psi	56 ÷ 63 kg 118 > 139 lbs	5 bar 70 psi	50 ÷ 59 kg 122 > 139 lbs	4,2 bar 61 psi	50 ÷ 59 kg 122 > 139 lbs	3,6 bar 52 psi
61 ÷ 69 kg 164 > 198 lbs	6,3 bar 91 psi	64 ÷ 76 kg 175 > 196 lbs	5,7 bar 80 psi	64 ÷ 74 kg 140 > 168 lbs	5,3 bar 75 psi	60 ÷ 69 kg 140 > 165 lbs	4,5 bar 65 psi	60 ÷ 69 kg 140 > 165 lbs	4 bar 58 psi
> 70 kg 199 > 218 lbs	6,5 bar 94 psi	≥ 77 kg 197 > 216 lbs	6 bar 85 psi	75 ÷ 85 kg ≥ 169 lbs	5,7 bar 80 psi	70 ÷ 79 kg 165 > 187 lbs	4,8 bar 70 psi	70 ÷ 79 kg 165 > 187 lbs	4,3 bar 62 psi
				≥ 86 kg ≥ 189 lbs	6 bar 85 psi	≥ 80 kg ≥ 188 lbs	5 bar 73 psi	80 ÷ 89 kg ≥ 188 lbs	4,6 bar 67 psi
								> 90 kg ≥ 198 lbs	5 bar 73 psi
TUBE TYPE									
24-622 700x24c		26-622 700x26c		28-622 700x28c		32-622 700x32c		35-622 700x35c	
Rider weight (kg/lbs)	Pressure (bar/psi)	Rider weight (kg/lbs)	Pressure (bar/psi)	Rider weight (kg/lbs)	Pressure (bar/psi)	Rider weight (kg/lbs)	Pressure (bar/psi)	Rider weight (kg/lbs)	Pressure (bar/psi)
< 45 kg ≤ 115 lbs	6 bar 87 psi			≤ 53 kg ≤ 117 lbs	5 bar 70 psi	≤ 44 kg ≤ 97 lbs	4 bar 58 psi	≤ 44 kg ≤ 106 lbs	3,5 bar 51 psi
45 ÷ 52 kg 116 > 134 lbs	6,3 bar 91 psi	≤ 52 kg ≤ 115 lbs	5,7 bar 80 psi	54 ÷ 60 kg 118 > 132 lbs	5,3 bar 75 psi	44 ÷ 49 kg 98 > 117 lbs	4,3 bar 62 psi	45 ÷ 49 kg 107 > 121 lbs	3,7 bar 54 psi
53 ÷ 60 kg 135 > 163 lbs	6,5 bar 94 psi	53 ÷ 61 kg 116 > 134 lbs	6 bar 85 psi	61 ÷ 68 kg 133 > 150 lbs	5,7 bar 80 psi	50 ÷ 59 kg 118 > 139 lbs	4,5 bar 65 psi	50 ÷ 59 kg 122 > 139 lbs	4 bar 58 psi
61 ÷ 69 kg 164 > 198 lbs	6,8 bar 99 psi	62 ÷ 74 kg 135 > 163 lbs	6,3 bar 90 psi	69 ÷ 79 kg 151 > 174 lbs	6 bar 85 psi	60 ÷ 69 kg 140 > 168 lbs	4,9 bar 71 psi	60 ÷ 69 kg 140 > 165 lbs	4,3 bar 62 psi
70 ÷ 76 kg 199 > 218 lbs	7,3 bar 106 psi	75 ÷ 90 kg 164 > 198 lbs	6,7 bar 95 psi	80 ÷ 89 kg 175 > 196 lbs	6,3 bar 90 psi	70 ÷ 79 kg ≥ 169 lbs	5,2 bar 75 psi	70 ÷ 79 kg 165 > 187 lbs	4,7 bar 68 psi
77 ÷ 85 kg ≥ 219 lbs	7,6 bar 110 psi	91 ÷ 108 kg 199 > 218 lbs	7 bar 100 psi	90 ÷ 98 kg 197 > 216 lbs	6,7 bar 95 psi	80 ÷ 89 kg ≥ 169 lbs	5,5 bar 78 psi	80 ÷ 89 kg ≥ 188 lbs	5 bar 73 psi
> 86 kg ≥ 219 lbs	8 bar 116 psi	≥ 109 kg ≥ 219 lbs	7,3 bar 105 psi	≥ 99 kg ≥ 217 lbs	7 bar 100 psi	≥ 90 kg ≥ 198 lbs	5,8 bar 84 psi	> 90 kg ≥ 198 lbs	5,4 bar 78 psi

DEPENDING ON RIDING STYLE

- COMFORT > drop 0,3 bar / 5 psi on FRONT wheel
- AGGRESSIVE > keep same pressure front and rear
- If wet and/or cold road conditions (below 7°C / 44F) drop 0,3 bar / 5 psi on BOTH wheels



NEVER EXCEED THE MAXIMUM INFLATION PRESSURE INDICATED ON EITHER THE RIM, THE RIM TAPE and THE TYRE